



Máquina roscadora con incorporador de punteadores

SASPI					PEINES WATERBURY				POTEN.	VELOCI.	PESO	
	Ø Min.	Max.	L. Min.	Max.	Nº	L1	L2	S	H	KW	P / MIN.	Kg.
RGVP2	2	8	6	100	10	4-1/4"	5"	15/16"	2-1/8"	14	80-250	6400
RGVP3	4	12	10	130	20	7"	8"	1-3/16"	3-1/8"	22	60-250	7600
						152.4	171.45	30.15	79.4			
RGVP4	4	14	10	150	30	7-1/2"	8-1/2"	1-7/16"	4-1/8"	32	50-200	9400
						190.5	215.9	36.5	104.8			
RGVP5	5	18	15	200	40	9"	10"	1-11/16"	4-1/8"	40	40-160	14000
						228.6	254	42.85	104.8			
RGVP6	8	22	20	250	50	11"	12"	1-15/16"	5-1/8"	48	30-120	19500
						279.4	304.8	49.2	130.2			
RGVP8	10	26	25	250	60	15"	16"	2-3/16"	6-5/8"	60	25-100	30400
						381	406.4	55.55	168.3			
RGVP9	12	35	25	400	70	19"	20"	2-7/16"	7"	60	25-80	36100
						482.6	508	61.91	177.8			
RGVP10	15	45	25	400	100	26"	27"	3"	7"	70	25-50	43000
						660.4	685.8	76.2	177.8			